**COMPLIANCE REPORT** 

TO

THE CONDITIONS

OF

**ENVIRONMENTAL CLEARANCE ORDER** 

NO: 946/SEIAA/EC1/4152/2015

DT. 16 - 08 - 2017

BY

STATE ENVIRONMENT IMPACT ASSESSMENT AUTHORITY (SEIAA)

**FOR** 

PROPOSED QUARRY PROJECT

**AT** 

SURVEY NO. 59/2. KARIAVATTOM VILLAGE, VETTATHOOR
PANCHAYAT, PERINTHALMANNA TALUK, MALAPPURAM DISTRICT,
KERALA

BY

POABSON GRANITE PRODUCTS PRIVATE LIMITED
KUTTOOR P.O., THIRUVALLA PATHANAMTHITTA - 689016

(October, 2019 - March, 2020)

#### **INTRODUCTION**

M/s Poabson Granite Products Pvt. Ltd. is a stone quarry situated at Survey No. 59/2, Kariavattom Village Vettathoor Panchayat – Perinthalmanna Taluk, Malappuram District, Kerala. The quarry project has accorded with the environmental clearance by state Environmental Impact Assessment Authority on 16-08-2017. Six monthly compliance reports to the conditions of the environmental clearance are to be submitted as part of compliance. The compliance report to the specific and general conditions of the environmental clearance for the period of October, 2019 – March, 2020 is being submitted.

# PART A - SPECIFIC CONDITIONS

# Condition 1

If any plant species endemic to Western Ghats are noticed in the area, they shall be properly protected in situ or by transplanting to an appropriate location inside the lease area.

# ✓ Compliance

Most of the land area covering under the present EC are already under mining activities. Thus the loss of endemic plant species are very negligible regarding the present project. The Company properly protecting the plant species that are endemic to Western Ghats in situ or by transplanting to an appropriate location. Company also plan to develop a plant Nursery for the native plants including the endemic species for plantation purposes.

#### **PART B – GENERAL CONDITIONS**

#### Condition 1

Rainwater harvesting facility should be installed as per the prevailing provisions of KMBR/KPBR unless otherwise specified.

# √ Compliance

Regarding the current mining project, a mined out pit is using as rainwater storage system having the capacity of 12000000 liters. Photograph showing the same is enclosed as Annexure 1. Details of the rainwater harvesting system are as follows.

,	SI. No.	Туре	Length	Width	Height	Capacity
			(m)	(m)	(m)	(L)
	1	Excavated mine pit	50	40	6	12000000

#### Condition 2

Environment Monitoring Cell as agreed under the affidavit filed by the proponent should be formed and made functional.

# ✓ Compliance

An environmental monitoring cell was formed with Mr. K.A Abraham (Managing Director of the Company) as head. Meeting of the monitoring cell has been arranging monthly since the starting of the project and discussing the status of the compliance of the specific and general conditions stated in the Environmental clearance order. The details of the monitoring cell members are given below.

SI. No.	Post	Name
1	Head of the monitoring cell (Managing Director of the Company)	Mr. K.A Abraham
2	Head in charge (Environment)	Mr. Girish Menon
3	Senior Environmental Officer	Dr. Rinoy Varghese
4	Environmental Officer	Mr. Navin Xavier

5	Name of the environmental officer in charge at site	Mr. Raghu
6	Name of the officer Environment, Health and safety at site.	Mr. Mathew
7	Name of the environmental consultant	M/s Environmental Engineers & Consultants Pvt. Ltd.
8	Address of Environmental laboratory	M/s Poluchem Laboratory Pvt. Ltd.

Suitable avenue trees should be planted along either side of the tarred road and, open parking areas if any, including approach road and internal roads.

# √ Compliance

Open parking areas and sides of the tarred roads are almost covered by natural vegetation and the vacant spaces including the sides of approach road and other places near to the project area has planted with tree saplings. The photographs showing the same are attached as Annexure No.2.

#### Condition 4

Maximum possible solar energy generation and utilization shall done at the own cost of the project proponent.

#### ✓ Compliance

Regarding the present project, the Company has incorporated solar devices for energy generation and utilization. A total of ten solar lights has erected along the road sides, magazine area, office area, crusher units etc. Solar heaters has provided in the canteen and is used for water boiling. Photographs showing solar energy devices are given in Annexure 3.

Sprinklers shall be installed and used in the project site to contain dust emission.

# ✓ Compliance

The road system of the project site, approach road and other connected roads has been watering daily by sprinkler system installed in tipper lorry since the starting of the project. For the suppression of the dust generated during Crushing & Screening operation, Company has installed fixed water sprinkling systems in the Crushing units. Dust emission during drilling process are reducing by wet sack. Photographs showing sprinkler system installed in the crusher unit and tipper lorry is enclosed as Annexure 4.

#### Condition 6

Eco-restoration including the mine closure plan shall be done at the own cost of the project proponent.

# ✓ Compliance

Subsequent to the closing of the mine, ten percent of the excavated pit area will be retained as water storage area. It is proposes to develop a green belt in the remaining area after reclaimed with stacked dumping and overburden. As part of the same, we have stored the top soil and overburden in a prefixed area and started planting. Eco-restoration including the mine closure plan will be perform at Company own cost.

# Condition 7

At least 10 percent out of the total excavated pit area should be retained as water storage area and the remaining area should be reclaimed with stacked dumping and overburden and planted with indigenous plant species that are eco-friendly, if no other specific condition on reclamation of pit is stipulated in the E.C.

# ✓ Compliance

The project team will retain ten percent of the excavated pit area as water storage area following to the closure of the mine. It is proposes to develop a green belt in the remaining area with indigenous plant species after reclaimed with stacked dumping and overburden. Grass and Shrub species with strong root system will plant in the areas prone to erosion especially at the foot of the hill.

#### Condition 8

Corporate Social Responsibility (CSR) agreed upon by the proponent should be implemented.

# √ Compliance

As part of the Corporate Social Responsibility, the amount proposed by the company has been spending for various social activities. The Major CSR activities includes Public road maintenance, materials supply for construction works, marriage support, donation to socio cultural activities, medical aid, education aid etc.

#### Condition 9

The lease area shall be fenced off with barbed wires to a minimum height of 4ft around, before starting of mining. All the boundary indicators (boards, stores, markings, etc.) shall be protected at all times and shall be conspicuous.

#### ✓ Compliance

Barbed metal wire fencing has installed around the mining area with a height of 4 ft to prevent falling of animals/human/belongings/dumping of garbage's etc. All the boundary indicators (boards, stores, markings, etc.) are protecting. The photograph showing the same is attached as Annexure No.5

#### Condition 10

Warning alarms indicating the time of blasting (to be done at specific timings) has to be arranged as per stipulation of Explosive Department.

# √ Compliance

Warning alarm has installed in the project area and maintaining properly. The blasting time has fixed and is between 1.0pm and 2.0pm. A danger board indicating blasting time has also installed in the project site.

#### Condition 11

Control measures on noise and vibration prescribed by KSPCB should be implemented.

# ✓ Compliance

# **Noise pollution**

# **Mitigation measures Implemented**

The major noise generating source from the mining activity is working machinery, drilling, blasting and plying of vehicles. The following control measures are undertaken to bring down the noise levels:-

- Proper maintenance of machinery, equipment and improvement of design of machines.
- > Personal protective devices i.e., earmuffs, ear plugs etc. are provided to workers working in high noise areas.
- Maintain a wide green belt of dense foliage between mine areas and residential colonies.
- > The mining area is working only during day times.
- Noise quality is checking periodically. The sound levels are monitored through an NABL accredited laboratory during the quarry in operation and the monitored results are well within the permissible limits.

#### Blast vibrations and control measures

- Controlled blasting technique is adopted in this project in order to reduce blast vibrations.
- **❖** Non Electric Detonators are using for blasting activities.
- ❖ The maximum charge per delay is not more than 10kg to limit the PPV values to 10mm/sec.

❖ Optimum delay sequence and stem to column ratio is maintaining to minimize the ground vibration intensity.

#### Condition 12

Quarrying activities should be limited to day time as per KSPCB guidelines/specific conditions.

# ✓ Compliance

Quarrying activities are carrying out only during day time.

#### Condition 13

Blasting should be in a controlled manner as specified by the regulations of Explosive department or any other concerned agency.

# ✓ Compliance

# Blasting

- ❖ Non electric Detonators (NONEL) are using for blasting
- ❖ The controlled blasting is proposed by adopting all the safety measures as per "MMR 1961" and with the permission of DGMS.
- ❖ Blasting is carried out for the fragmentation of the granite within the project area. Multiple blast holes of 1.0 to 1.5 m depth has drilled with the help of 32mm drill rod, Jack Hammer and air compressor of 100 cm capacity.
- ❖ It is estimated about 250g of explosives per hole is required. About 30-50 holes per blast are proposed. Therefore the requirement of explosive will be about 10kg/ blast.

#### Blasting safeguard

- Blasting in the open cast is done only during day time at designated hours.
- Only competent blasters are appointed to handle explosives.
- Explosives are stored in approved and licensed magazine as per explosive Act/ Rules.
- ❖ Explosives are brought from magazine to blasting site in licensed explosive van under the care of blaster.

- ❖ Sufficient warning signals are given before blasting the holes.
- ❖ Guards are posted on all roads and paths at least 250 m distance to stop entrance to the danger zone during the blasting hour.
- Controlled blasting is practiced to control vibrations and flying fragments.
- ❖ Optimum charge is used, while blasting near office complex/ infrastructure site.
- ❖ Maximum charge per delay is always being less than 10kg to limit the PPV levels within the DGMS standards of 15 mm/sec.

A licensed person should supervise/ control the blasting operations.

# ✓ Compliance

Licensed persons are supervising/controling the blasting operations. Certificate of the licensed person is attached as Annexure 6.

#### > Condition 15

Access road to the quarry shall be tarred to contain dust emissions that may arise during transportation of materials.

#### ✓ Compliance

Access road to the quarry has tarred and maintaining well to contain dust emissions that may arise during transportation of materials. The photographs showing the same is given in Annexure 7.

#### Condition 16

Overburden materials should be managed within the site and used for reclamation of mine pit as per mine closure plan/ specific condition.

# ✓ Compliance

The excavated top soil is storing in a prefixed location for the reclamation of mine pit as per mine closure plan/specific condition. Overburden/topsoil dump has properly protected by applying geotextiles, plantation, making trenches/footwalls etc. Photograph showing the Overburden/topsoil dump is attached as Annexure 8.

Height of the benches should not exceed 5m, and width should not be less than 5m, if there is no mention is the mining plan/ specific condition.

# ✓ Compliance

Mining operation is carrying out in the form of benches. The proposed height and width of the benches are maintaining. The photograph showing the bench type mining is enclosed as Annexure 9.

#### Condition 18

Mats to reduce fly rock blast to a maximum of 10 PPV should be provided.

# ✓ Compliance

Several safety measures are practicing to prevent fly rocks cross the lease area. Blasting during unfavorable weather conditions has avoided. Maintain optimum delay sequence and stem to column ratio to minimize the fly rock distance. Mats to prevent fly rock during blasting are also provided.

#### Condition 19

Maximum depth of mining from general ground level at site shall not exceed 10 m.

# ✓ Compliance

Mining depth will not exceed beyond 10m from general ground level.

#### Condition 20

No mining operation should be carried out at places having a slope greater than 45.

#### ✓ Compliance

Mining operations are not carrying out at regions having a slope greater than 45°

#### Condition 21

Acoustic enclosures should have been provided to reduce sound amplifications in addition to the provisions of green belt and hollow brick envelop for crushers,

so that the noise level is kept within prescribed standards given by CPCB/KSPCB.

# ✓ Compliance

The entire project area has covered by thick green belt and this will reduce sound amplifications produced during mining activities. The noise level are limiting within the prescribed standards given by CPCB/KSPCB.

#### Condition 22

The workers on the site should be provided with the required protective equipment such as ear muffs, helmets, etc.

# ✓ Compliance

Workers are provided with personal protective devices such as earmuffs, ear plugs, helmet etc.

#### Condition 23

Garland drains with clarifiers to be provided in the lower slopes around the core area to channelize storm water.

# √ Compliance

From the entire project area, storm water is channelizing in to an excavated pit and stored the storm water in it. During this storage all the debris/slit in the storm water will be sedimented in to the bottom of the pit. Overflow from the storm water pit are opens to drainage systems with silt traps. Photographs showing the same is attached as Annexure 10.

#### Condition 24

The transportation of minerals should be done in covered trucks to contain dust emissions.

#### ✓ Compliance

After loading, trucks are covered with tarpaulin sheets to control dust emissions during transportation. Moreover, trucks are not overloading and the loads are maintained to the body level.

#### **≻** Condition 25

The proponent should plant at least 5 times of the loss that has been occurred while clearing the land for the project.

# ✓ Compliance

Most of the land area covering under the present EC are already under mining activities. Thus the loss of vegetation are very negligible regarding the present project. We are planting tree saplings 5 times of the loss that has been occurred while clearing the land for the project.

#### Condition 26

Disposal of spend oil from diesel engines should be as specified under relevant rules/regulations.

# ✓ Compliance

Disposal of spent oil from diesel engines are carrying out under relevant rules/regulations.

#### Condition 27

Explosive should be stored in magazines in isolated place specified and approved by the Explosive Department.

#### ✓ Compliance

Explosives are storing in magazines built in an isolated place specified and approved by the Explosives Department. Photograph showing the same is attached as Annexure 11.

#### Condition 28

A minimum distance of 100 m from the boundary of the quarry to the nearest dwelling unit or other structures, not being any facility for mining shall be provided.

#### ✓ Compliance

Distance of 100m from the boundary of the quarry to the nearest dwelling unit or other structures has provided.

#### Condition 29

100 m buffer distance should be maintained from forest boundaries.

# √ Compliance

Distance criteria as per SEIAA from the boundary of the quarry to the forest are provided.

#### Condition 30

Consent from Kerala State Pollution Control Board under Water and Air Act(s) should be obtained before initiating mining activity.

# ✓ Compliance

Consent from Kerala State Pollution Control Board under Water and Air Act(s) has obtained. Consent Order from Kerala State Pollution Control Board is attached as Annexure 12.

#### Condition 31

All other statutory clearances should be obtained as applicable by project proponents from the respective competent authorities including that blasting and storage of explosives.

# ✓ Compliance

All other statutory approvals required for the quarrying activity has obtained for the project. The details regarding the same along with the copy of the statutory approvals are enclosed as Annexure 8 and 9. Details of statutory approvals are given below.

SI. No.	Annexure	Statutory approvals
1	13	License from Panchayat
2	14	License to possess: (c) for use, explosives of class1, 2, 3, 4, 5, 6 or 7.

#### Condition 32

In the case of any change(s) in the scope of the project, extent quantity, process of mining technology involved or in any way affecting the environmental parameters/impacts are assessed, based on which only the E.C. is issued, the **Poabson Granite Products Pvt. Ltd.** Fifth Compliance Report

project would require a fresh appraisal by this Authority for which the proponent shall apply and get the approval of this authority.

# ✓ Compliance

# We are agreed

# > Condition 33

The Authority reserves the right to add additional safeguard measures subsequently if found necessary, and to take action including revoking of the environmental clearance under the provisions of the Environmental (Protection) Act, 1986 to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.

# √ Compliance

# We are agreed

#### Condition 34

The stipulation by the statutory authorities under different acts and notifications should be complied with including the Water (Prevention and Control of Pollution) Act 1974, The Air (Prevention and Control of Pollution) Act, 1981, The Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification 2006.

#### ✓ Compliance

# Would be complied

#### Condition 35

The project Proponent should advertise in at least two local newspapers widely circulated in the region one of which (both the advertisement and the newspaper) shall be in the vernacular language informing that the project has been accorded Environmental Clearance and copies of clearance letters are available with the State Environmental Impact Assessment Authority (SEIAA) office and may also be seen on the website of the Authority at <a href="https://www.seiaa.kerala.org">www.seiaa.kerala.org</a>. The advertisement should be made within 10 days from the date of receipt of the clearance letter and the copy of the same signed in all pages should be forwarded to the office of the Authority as confirmation.

# √ Compliance

Regarding the accordance of environmental clearance to the quarrying activity has advertised in two local newspapers and the copy of the same was submitted to SEIAA Kerala. The copies of the advertisements are provided at Annexure 15 & 16. Details of the newspaper advertisements are given below.

SI. No.	Annexure	Name of the Newspaper and edition	Dated
1	15	New Indian Express	27/08/2017
2	16	Mathrubhumi	27/08/2017

#### Condition 36

A copy of the clearance letter shall be send by the proponent to concerned Grama panchayat/ District panchayat/ Muncipality/ Corporation/ Urban local body and also to the Local NGO if any, from whom suggestions/ representations if any, were received while processing the proposal. The Environmental Clearance shall also be put on the website of the company by the proponent.

#### ✓ Compliance

A copy of the environmental clearance order was submitted to the Panchayat office. The acknowledgement received is provided at Annexure 17. There is no suggestion/representation received so far from anybody. The environmental clearance order is uploaded in the website of the company and can be seen in the website www.msand.in

#### Condition 37

The proponent shall submit half yearly reports on the status of compliance of the stipulated E.C. conditions including results of monitored data (both in hard copies as well as by e- mail) and upload the status of compliance of the stipulated E.C. conditions, including result of monitored data on website and shall update the same periodically. It shall simultaneously be send to the respective Regional office, of MOEF, Govt. of India and also to the State Environmental Impact Assessment Authority (SEIAA) office.

# √ Compliance

Fifth compliance report is being submitted to SEIAA, Department of Environment and Climate change, Govt. of Kerala and Regional Office of MoEF, Govt. of India both in hard copy as well as soft copy (CD).

#### Condition 38

The details of environmental clearance should be prominently displayed in a metallic board of 3ft x 3ft with green background and yellow letters of Times New Roman font of size of not less than 40. Sign board with extent of lease area and boundaries shall be depicted at the entrance of the quarry visible to the public.

# ✓ Compliance

Details of the environmental clearance prominently displayed in a metallic board of 3 ft x 3 ft with green background and yellow letters of Times New Roman fond has installed.

#### Condition 39

The proponent should provide notarized affidavit (indicating the number and date of environmental clearance proceedings) that all the conditions stipulated in the E.C. shall be scrupulously followed.

#### ✓ Compliance

An affidavit stating that all the conditions stipulated in the Environmental clearance will be scrupulously followed has submitted to Department of Environment and climate change and the copy of the same is attached at Annexure 18.

#### Condition 40

No change in mining technology and scope of work should be made without prior approval of the SEIAA, No further expansion or modifications in the mines shall be carried out without prior approval of the SEIAA, as applicable.

# ✓ Compliance

We will not make any change in mining technology and scope of work without prior approval of the SEIAA and further expansion or modifications in the mines will not be carried out without prior approval of the SEIAA.

#### Condition 41

The project proponent shall ensure that no natural water course and/or water recourses shall be obstructed due to any mining operations. Necessary safe guard measures to protect the first order streams if any, originated from the mine lease shall be taken.

# ✓ Compliance

We ensure that no natural water course and/or water recourses has not obstructed due to any mining operations. There is no first order streams originated from the mine lease.

#### Condition 42

Monitoring of Ambient Air Quality to be carried out based on the notification 2009, as amended from the time to time by the Central Pollution Control Board. Water sprinkling should be increased at places loading and unloading points and transfer points to reduce fugitive emission.

# ✓ Compliance

We are carrying out monitoring of Ambient Air Quality based on the notification 2009, as amended from the time to time by the Central Pollution Control Board. Water sprinkling has installed at places via loading and unloading points and transfer points to reduce fugitive emission.

#### Condition 43

The top soil, if any, shall be temporarily be stored at earmarked site(s) only for the top soil shall be used for land reclamation and plantation. The overburden generated during the mining operation shall be stacked at earmarked dump site(s) only. The maximum height of the dump shall not exceed 8m and width 20m and overall slope of the dump shall be maintained to 45°. The O.B. dump should be scientifically vegetated with suitable native species to prevent erosion and surface run off. In critical areas, use of geo textiles shall be undertaken for the stabilization of the dump. The entire excavated area shall be backfilled. Monitoring and management of rehabilitated area should continue until the vegetation become self-sustaining.

# ✓ Compliance

The area has earmarked for dumping the overburden generated during the mining operation. The maximum height of the dump will not exceed 8m and width 20m and overall slope of the dump will be maintained to 45°. The O.B. dump is scientifically stabilizing by geotextile and suitable native plant species to prevent erosion and surface run off. The entire excavated area will be backfilled. We will monitor and manage the rehabilitated area until the vegetation become self-sustaining.

#### Condition 44

Catch drains and siltation ponds of appropriate site shall be constructed around the mine working mineral and O.B. dumps to prevent runoff water and flow of sediments directly into the river and other water bodies. The water so collected should be utilized for watering the mine area, roads, green belt development etc. The drains shall be regularly desilted particularly after monsoon and maintained properly.

#### ✓ Compliance

Catch drains and siltation ponds at appropriate site has constructed for the mine working, mineral and O.B. dumps to prevent runoff water and flow of sediments directly into the river and other water bodies. The water so collected are using for watering the mine area, roads, green belt development etc. The drains are regularly desilted particularly after monsoon and maintained properly.

Effective safe guard measures such as regular water sprinkling shall be carried out in critical areas porn to air pollution and having high levels of  $PM_{10}$  and  $PM_{25}$  such as haul road loading and uploading points and transfer points. It shall be ensure that the Ambient Air Quality Parameters conform to the norms prescribed by the Central Pollution Control Board in this regard.

# ✓ Compliance

Effective safe guard measures such as regular water sprinkling are carrying out in critical areas porn to air pollution and having high levels of PM<sub>10</sub> and PM<sub>25</sub> such as haul road loading and uploading points and transfer points. It is ensuring that the Ambient Air Quality Parameters conform to the norms prescribed by the Central Pollution Control Board in this regard.

#### Condition 46

Fugitive dust emission from all the sources should be controlled regularly. Water spraying arrangements on haul roads, loading and unloading at transfer points. Should be provided and properly maintained.

#### ✓ Compliance

Fugitive dust emission from all the sources are controlling regularly. Water spraying arrangements on haul roads, loading and unloading at transfer points has arranged and properly maintained.

#### Condition 47

Measures should be taken for the control of Noise level below 85 DBA in the work environment.

#### ✓ Compliance

Different measures will be taken for the control of noise level below 85 DBA in the work environment. We are also checking the Ambient Sound level periodically.

A separate Environment Management Cell with suitable qualified personal should be setup under the control of a senior executive who will directly report to the head of the organization.

# √ Compliance

A separate Environment Management Cell with suitable qualified personal has formed under the control of a senior executive who will directly report to the head of the organization.

#### Condition 49

The funds earmarked for the Environmental protection measures and CSR activities should be kept in separate account and should not be diverted for other purpose. Year wise expenditure should be reported to the State Environmental Impact Assessment Authority (SEIAA) office.

# ✓ Compliance

The funds earmarked for the Environmental protection measures and CSR activities are not diverting for other purpose. We will reports year wise expenditure to the State Environmental Impact Assessment Authority (SEIAA) office.

#### Condition 50

The regional office of MOEF and CC located at Bangalore shall monitor compliance of the stipulated conditions. The project Authorities should extent full co-operation to the officer (s) of the regional office by furnishing the requisite data/information/monitoring reports.

#### ✓ Compliance

We will extent full co-operation to the MOEF officer (s) of the regional office by furnishing the requisite data/information/monitoring reports.

#### Condition 51

Any appeal against the Environmental Clearance shall lie with the National Green Tribunal, if preferred within a period of 30 days as prescribed under section 16 of the National Green Tribunal Act, 2010.

# √ Compliance

# There is no appeal against this Environmental Clearance with the National Green Tribunal.

#### Condition 52

Concealing the factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in the withdrawal of this clearance and attract action under the provision of Environmental Protection Act, 1986.

# √ Compliance

# We agreed

#### Condition 53

The SEIAA may revoke, or suspend the order for non-implementation of any of the specific or this implementation of any of the conditions is not satisfactory. The SEIAA reserves the right to alter/modify the above conditions or stipulate any further conditions or stipulate any further conditions in the interest of Environmental Protection.

# √ Compliance

# We agreed

# > Condition 54

The above conditions shall prevail not withstanding anything to the contrary in consistent or simplified, contained in any other permit, license on consent given by any other authority for any other project.

# ✓ Compliance

#### We agreed

#### Condition 55

The order is valid for a period of 5 years or the expiry date of mining lease period issued by the Government of Kerala, whichever is earlier.

#### ✓ Compliance

#### We agreed

The Environmental Clearance will be subject to the final order of the courts in any pending litigation related to the land or project, in any court of law.

# ✓ Compliance

There is no pending litigation related to the land or project, in any court of law regarding this project.

#### Condition 57

The mining operation shall restrict to above ground water table and it should not intersect ground water table.

# ✓ Compliance

We are carrying out mining activity above the ground water table only and it will not intersect ground water table.

#### Condition 58

All vehicles used for transportation and within the mine shall have 'PUC' certificate from authorized pollution taking center. Washing of all vehicles shall be in the lease area.

# ✓ Compliance

All vehicles using for the transportation within the mine have obtained 'PUC' certificate from authorized pollution taking center. All the vehicles will be washed within in the lease area only.

#### Condition 59

Project proponent should obtain necessary prior permission of the competent authorities for withdrawal of requisite quantity of surface water and ground water for the project.

# ✓ Compliance

For the current project we are using harvested rainwater for all domestic and industrial purposes. We will obtain necessary prior permission of the competent authorities for withdrawal of surface water and ground water for the project at the time of usage of the same.

Regular monitoring of flow rates and water quality upstream and down streams of the spring and perennial nallahs flowing in and around the mining lease area shall be carried out and reported in the six monthly reports to the SEIAA.

# ✓ Compliance


We are monitoring the flow rates and water quality upstream and down streams of the spring and perennial nallahs flowing in and around the mining lease.

#### Condition 61

Occupational Health surveillance programme of the workers should be under taken periodically to observe any contractions due to exposure to dust and take corrective measures if needed.

# ✓ Compliance

We are carrying out Occupational Health surveillance programme of our workers periodically to observe any contractions due to exposure to dust and take corrective measures if needed in connection with Mines Vocational Training.



Photograph showing abandoned Mined out pit using as rainwater storage system





Photographs showing tree planted around parking areas and road sides


Poabson Granite Products Pvt. Ltd.

Fifth Compliance Report





Photograph showing the Solar Energy device installed within the project area






Photograph showing the Sprinkler system installed in crusher plant and tipper lorry



Photograph Showing the Barbed metal wire fencing installed around the mining area





Photograph showing the tarred Access road to the quarry





**Poabson Granite Products Pvt. Ltd.** 





Photograph showing the Overburden/topsoil dump stabilized by geotextiles and vegetation



Photograph showing the bench type mining






Photographs showing Storm water pit and Garland drain

# **Annexure 11**





**Photograph showing Explosive Magazines** 

# **Annexure 12**

FILE NO: 1187892 Date of issue: 26/12/2017



#### KERALA STATE POLLUTION CONTROL BOARD

#### CONSENT TO

#### OPERATE/AUTHORISATION/REGISTRATION

#### ISSUED UNDER

The Water (Prevention & Control of Pollution) Act, 1974 The Air (Prevention & Control of Pollution) Act, 1981

and

The Environment (Protection) Act, 1986

As per Application No. :1187892 Dated:22-12-2017

TO

M/s POABSON GRANITE PRODUCTS (P) LTD(QUARRY)
THELAKKAD.PO, PERINTHALMANNA, MALAPPURAM.DT

Consent No. :PCB/CO/7633/17 Valid Upto :30/11/2022

Page

## 1. GENERAL

1.1. This integrated consent is granted subject to the power of the Board to withdraw consent, review and make variation in or revoke all or any of the conditions as the Board deems fit.

1	VALIDITY	30/11/2022
2	Name and Address of the establishment	POABSON GRANITE PRODUCTS (P) LTD(QUARRY) THELAKKAD.PO, PERINTHALMANNA, MALAPPURAM.DT 679325
3	Communication	Telephone :04933-276300 Fax :- E-mail:pmna@poabs.in
4	Occupier Details	SRI.K.A.ABRAHAM, MANAGING DIRECTOR, M/S POABSON GRANITE PRODUCTS (P) LTD THELAKKAD.PO, PERINTHALMANNA, MALAPPURAM.DT
5	Local Body	VETTATHUR
6	Survey Number	59/2
7	Village	KARYAVATTOM
8	Taluk	PERINTHALMANNA
9	District	MALAPPURAM
10	Capital Investment(Rs in Lakhs)	1000.0/-
11	Scale	Medium
12	Category	RED
13	Annual fee(Rs)	75000/-
	Total Fee remitted(Rs)	412500/-
14	RAW MATERIAL	PRODUCTS
		BLASTED RUBBLES @5 Metric Tonnes/DAY (Quarrying in 4.5000 hectares of land in survey no 59/2 of Kariavattom village Perinthalmanna Taluk, Malappuram Dist)
15	Total Power Required (HP)	NIL

## 2. CONDITIONS AS PER

The Water(Prevention and Control of Pollution)Act, 1974

2.1 In case of generation of trade effluent from the industry, effluent treatment system consisting of treatment units having adequate capacity established as per the Integrated Consent to Establish issued shall be operational at all times during which the industry is functional. Additional facilities required, if any, to achieve the standards laid down by the Board u/s 17(1) (g) of the Water Act shall also be made along with.

Page2

2.2	Water consumption: NIL					
2.3	Effluent generation:					
2.4	The characteristics o	f effluent after treatme	ent shall confir	m to the follow	ing tolerance limits:	
SI.NO.	Characteristics	Unit	Tole	rance Limit		
			Sew	age	Trade Effluent	
2.5	Mode of disposal of	treated effluent: -				
	NDITIONS AS PER Air(Prevention and C	Control of Pollution	)Act, 1981			
3.1	Adequate air pollutio industry. Additional also be made along w	facilities required, if a	all be operation ny, to achieve	nal at all times of the standards la	during the functioning of the id down by the Board shall	
Stack S No.	Sources of Emission	Emission Rate(Nm3/Hr)	Stack Heig	it above	Control Equipment	
			Ground Level	Roof Level	).	
SI.No.		Parameter		Limitin	g Standards (mg/Nm3)	
4. CON	NDITIONS AS PER Environment (Protect The operation of the total (Regulation and Cont	tion) Act, 1986.	ly in complian		g Standards (mg/Nm3)	
4. CON	The operation of the (Regulation and Cont	tion) Act, 1986. industry shall be strict trol) Rules 2000.		ce with the prov		
4. CON The F	The operation of the total (Regulation and Contumer Used lead acid batter 2001) Hazardous waste general (Management and Tra	tion) Act, 1986. industry shall be strict trol) Rules 2000. ies shall be disposed o	f as per the Ba handled as per ent) Rules, 2016	teries (Manage	risions of the Noise Pollution ment and Handling) Rules,	
4.1 CON The I 4.1 4.2 4.3 4.3.1	The operation of the (Regulation and Cont Used lead acid batter 2001  Hazardous waste gen (Management and Tra Activities for which A	industry shall be strict trol) Rules 2000. ies shall be disposed of crated, if any, shall be ansboundary Moveme	f as per the Ba handled as per int) Rules, 2016	teries (Manage	risions of the Noise Pollution ment and Handling) Rules,	
4. CON The F 4.1 4.2 4.3	The operation of the (Regulation and Cont Used lead acid batter 2001 Hazardous waste gen (Management and Tr. Activities for which A	industry shall be strict trol) Rules 2000. ies shall be disposed of crated, if any, shall be ansboundary Moveme	f as per the Ba handled as per nt) Rules, 2016 d  transport	teries (Manage	risions of the Noise Pollution ment and Handling) Rules,	
4.1 CON The F 4.1 4.2 4.3 4.3.1	The operation of the (Regulation and Cont Used lead acid batter 2001  Hazardous waste gen (Management and Tra Activities for which /	industry shall be strict trol) Rules 2000. ies shall be disposed of crated, if any, shall be ansboundary Moveme	handled as per thandled as per th) Rules, 2016 d transport Storage	tteries (Manage the Hazardous	risions of the Noise Pollution ment and Handling) Rules,	
4.1 CON The F 4.1 4.2 4.3 4.3.1 Collection Reception	The operation of the (Regulation and Cont Used lead acid batter 2001  Hazardous waste gen (Management and Tr. Activities for which A	tion) Act, 1986. industry shall be strict trol) Rules 2000. ies shall be disposed of the dispo	transport Storage Reprocessing	tteries (Manage the Hazardous 5.	risions of the Noise Pollution ment and Handling) Rules,	
4.1 CON The F 4.1 4.2 4.3 4.3.1 Collection Reception Treatmen	The operation of the (Regulation and Cont Used lead acid batter 2001  Hazardous waste gen (Management and Tr. Activities for which A	tion) Act, 1986. industry shall be strict trol) Rules 2000. ies shall be disposed of crated, if any, shall be ansboundary Moveme Authorisation is granted to deep the control of the contr	transport Storage Reprocessing	tteries (Manage the Hazardous 5.	risions of the Noise Pollution ment and Handling) Rules, and Other Wastes	
4.1 4.2 4.3 4.3.1  Collection Reception Treatmen 4.3.2	The operation of the (Regulation and Cont Used lead acid batter 2001  Hazardous waste gen (Management and Tr. Activities for which Automotive of the Control	tion) Act, 1986. industry shall be strict trol) Rules 2000. ies shall be disposed of crated, if any, shall be ansboundary Moveme Authorisation is granted to deep for the control of the c	transport Storage Reprocession/disposal of	tteries (Manage the Hazardous 5.	ment and Handling) Rules, and Other Wastes es shall be as follows:	
4.1 4.2 4.3 4.3.1  Collection Reception Treatmen 4.3.2	The operation of the (Regulation and Cont Used lead acid batter 2001  Hazardous waste gen (Management and Tr. Activities for which Automotive of the Control	tion) Act, 1986. industry shall be strict trol) Rules 2000. ies shall be disposed of crated, if any, shall be ansboundary Moveme Authorisation is granted to deep for the control of the c	transport Storage Reprocession/disposal of	tteries (Manage the Hazardous 5.	risions of the Noise Pollution ment and Handling) Rules, and Other Wastes es shall be as follows:	
4.1 4.2 4.3 4.3.1  Collection Reception Treatmen 4.3.2	The operation of the (Regulation and Cont Used lead acid batter 2001 Hazardous waste gen (Management and Tra Activities for which /	tion) Act, 1986. industry shall be strict trol) Rules 2000. ies shall be disposed of crated, if any, shall be ansboundary Moveme Authorisation is granted to deep for the control of the c	transport Storage Reprocession/disposal of	tteries (Manage the Hazardous 5.	ment and Handling) Rules, and Other Wastes es shall be as follows:	
4.1 4.2 4.3 4.3.1  Collection Reception Treatmen 4.3.2	The operation of the (Regulation and Cont Used lead acid batter 2001 Hazardous waste gen (Management and Tra Activities for which /	tion) Act, 1986. industry shall be strict trol) Rules 2000. ies shall be disposed of crated, if any, shall be ansboundary Moveme Authorisation is granted to deep for the control of the c	transport Storage Reprocession/disposal of	tteries (Manage the Hazardous 5.	risions of the Noise Pollution ment and Handling) Rules, and Other Wastes es shall be as follows:	

4.4 E-waste shall be disposed off safely as per the E-Waste (Management)Rules, 2016.

### 5. SPECIFIC CONDITIONS

- 5.1. The location of the Quarry shall be as per the approved drawing attached.
- 5.2. The PM 2.5 in ambient air at the boundary shall not exceed 60 microgram/m3
- 5.3. For renewal of the consent in case of continuance of discharge/operation of the industry, application in the prescribed form shall be submitted through the web portal of the Board foOnline Consent Management
- & Monitoring System 3 months before the end of validity period. Late application will be accepted only with a fine /late fee as applicable.
- 5.4. Boundary shall be fenced before operation of quarrying activities.
- 5.5. The concentration of PM10 at the boundary shall not exceed 100 microgram/m3.
- 5.6. After extraction at the site is completed, the land may be used for rain water harvesting with protective barriers/any other suitable approved purpose or may be reclaimed.
- 5.7. The applicant shall comply with the instructions that the Board may issue from time to time regarding the prevention and control of air, water, land and sound pollution.
- 5.8. No change or alteration of the quarrying area is to be made without the prior written permission of the Board. Any change in the particulars furnished and/or in the identity of the occupier/authorized agent is to be intimated to the Board forthwith.
- 5.9. The ambient air quality measured at 1 m outside the boundary of the premises shall not exceed the ambient air quality applicable to the adjoining area.
- 5.10. The sound level measured at 1 m outside the boundary of the premises shall not exceed the ambient sound level applicable to the adjoining area.
- 5.11. Suitable species of trees and curtain plants shall be planted and maintained within and along the periphery of the premises, forming a green belt to improve the environment.
- 5.12. The consentee shall put up a sign board of size 6x4 ft. near the main entrance of the plant to display the name of the unit and important consent conditions.
- 5.13. Bench cutting method shall be adopted for quarrying.
- 5.14.Blasting shall be done with prior signals in specified time. No. of blasting shall not exceed 10nos. at a time.
- 5.15.Blasting and quarrying shall be done without causing any nuisance or damage to occupants of adjoining or neighbouring land or building or posing damage to health, life or property.
- 5.16. Mining below normal water table by continuous pumping shall be avoided in summer period(March, April, May) to prevent drinking water shortage in that area.
- 5.17. Noise creating activities such as drilling ,blasting,breaking,loading etc shall not be done during night time(6pm-6am).
- 5.18. The applicant shall submit copies of all relevant permits/lease/certificate/licences periodically to this office to ensure the validity of this consent.
- 5.19. The conditions in the Environmental clearance shall be complied.
- 5.20.All other statutory or necessary clearances from other concerned authorities shall be obtained before commencing any quarrying operations.
- 5.21.Minimum distance of 50m shall be maintained from boundary of quarrying area to residential building, places of worships, public buildings, public roads, river, lake, railway lines and bridges.
  Reference:-

Page4

1) Mining & Geology letter No.: 8704/M3/2017 DATED:02.11.2017

2) Explosive license No: E/SC/KL/22/10(E8569) DATED:27.03.2015

3) Environmental Clearance No.: 946/SEIAA/EC1/4152/2015 Dated:16.08.2017.

VINAYA K S Digitally signed by VINAYA K S Date: 2017.12.26 11:28:22 +05'30'

DATE:26/12/2017

SIGNATURE & SEAL OF ISSUING AUTHORITY ENVIRONMENTAL ENGINEER, DO, MALAPPURAM




To


## STOCK FILE

- 1. This digitally signed document is legally valid as per the Information Technology Act 2000
- 2. For verifying this document please go to krocmms.nic.in and search using date of issue/name of the unit/Application Number in "Consent Granted Applications" link in the home page of the Board's Online Consent Management and Monitoring System.

Page5



mmid B1 - 1/15-16	නාන් නොවැනි. (ගාන පාකාගයක්
1994 ലെ കേരളാ പഞ്ചായത്ത് രാൻ	ആക്ട് (1994 ലെ 13 )232, 233, 234, 254 എന്നി വകുപ്പുകൾ നടർന്നുള്ള ചട്ടങ്ങളും അനുസരിച്ചു കൊടുത്ത
(Friedwing chocks o	വൈസൻസ്
	න ය ය ය ක්රී ය ක්රී ය ක්රී ය ක්රී ක්රී ක්රී ක්රී ක්රී ක්රී ක්රී ක්රී
	ഒപ്പായ് പുക്ക് ഗാരനെറ്റ് ഒപ്പാ ഡമ്മ് സ്
ചെയ്യും മാത്രിവിലാസവും	enot as adolon - con o son, 1/8
	0275
	ചാറപ്പെട്ടിച്ച് വിവിധമിനം അന്വലുള്ളം
എന്താവശൂത്തിന് ലൈസന്റ്	Sando sars agmo es. Al asmos
ത്രതുവരിച്ചു എത്	कर्म निका का नाम के इस्ते के कार्य है के कार्य कार्य
eagleosiesie muus	VP V 207
oragent auriers	
മെല്യാൻസിൽറ കാലാവാധി	1. 4.2015 to 81.3. 2020
อังสะเบอล์สซ์ คอใหม่	120000/ajas source
. 0	(Creology, Pillation controll Board
Glassidia 1900 H.P.	no my water to usual (mulain) 2320
- 100 Marines   100 Marines	みないのかのかられ からいないわらいのの)
	7009 al (00)
ടെയിക്കുർ /	dispersion of the contract of
	Sharing Babu.P
mlmml (+ 1+ 2015	Land Banchara
19	Shrift Crary Shrif
34 K / 2000	Thelalicad (80),0126 Ph: 04933 245126



## LICENCE FORM LE-3

(See article 3(a) to (d) of Part 1 of Schedule IV of Explosives Rules, 2000

Licence to possess: (c) for use, explosives of class 1, 2.3,4,5,6 or 7 in a mag

Licence No.: E/SC/KL/22/10(E8569) Annual Fee Rs:4200/-

1. Licence is hereby granted to : Shri K.A. ABRAHAM MG. DIRECTC R (O

M/s. POABSON GRANITE PRODUCT: PVT. LTD., The lakkad P.O. PERINTHALMANNA, MALAPPURAM DISTRICT, KERALA, 'own/Village - NILAMBUR

District-MALAPPURAM, State · Kerala, 'incode - 679325

Status of licensee: Individual

Licence is valid only for the following purpose: possess for use of Nitrate lixture, Safety Fuse,

4. (a) Licence is valid for the following kinds and quantity of explo

Sr. No.	Tana tala Description	Class & Division	T	Zaminity.
	Nitrate Mixture	2.0	(II all)	at any one time
2.	Safety Fuse	6.1		500 Kg.
3.	Detonators	6.2	0	30000 Mtrs
		0,3	0	20000 Nos.

(b) Quantity of explosives to be purchased in a calendar month[app leable for licence under article 3(b)

- 5. The licensed premises shall conform to the following drawing(s): Drawing No : E/SC/KL/22/10(E8569) dated : 12/05/1995
- The licensed premises are situated at following address:

Survey No(s). 59/1, Town/Village: KARYAVA ITOM

Police Station : MELATTOOR

PinCode:

Phone:

District : MALAPPURAM E-Mail:

State : Kerala Fax:

- 7. The licensed premises consist of following facilities: A magazinne with a hi, h exp. room and a
- The licence is granted subject to the provision of Explosives Act 188+ as amen ed from time to time and the Explosives Rules, 2008 framed there under anc the conditions, ad litional or aditions and the "-llowing Annexures.
  - Drawings (showing site, constructional and other details) as stated in serial 7 o. 5 above.

    (2) Conditions and Additional Conditions of this licence signed by the licensing authority.

  - (3) Distance Form DE-2
- 9. This licence shall remain valid till 31st day of March 2005

This licence is liable to be suspended or revoked for any violation of the Act or 7 ules framed there under r the conditions of this licence as set forth under Set VIII, wherever applicable, referred to in Part 4 of

									-
edule \	or if the license	C premises and							
nexure a	attached hereto.	c premises are not for	ind confe	rming to the	escription	shown in th	e plans and		
Date: 12	/05/1995								
	A CONTRACTOR OF THE PARTY OF TH				Joint Ch	ef Controll	er of Explosi	Sd/-	
ndment	s:					Sou	ith Circle, Che	ves mai	
mendme mendme	nt of Quantity of Exp	plosives/Monthly Purchase	e Limit dat	ed: 20/05/2011					
	Endorsement for a	plosives/Monthly Purchase plosives/Monthly Purchase enewal of licence:	e Limit dat	ed: 09/03/2012					
	Date of Renewal	The state of the s	11111	ODB ST. DO.		Service Control			
			-	Signature of	censing au	ority	300000		
	27/03/2015	31/03/2020	Dy. (	hief Controller	Explosiv	s. Emaloutes			
	2 SOUR	and the					And HILLS		
C.		AND DESCRIPTION OF	For Tree	Deputy Chief C कूलम / Erna	ontroller of	plosives			
Statutor	warning : Misha	ndling and misuse of exp	losives sh	all constitute s	rious cele-	and netter	NOT THE OWNER OF THE OWNER OW		
					ous trum	offence unc	fer the law.		
									(6)
									5 E
									7
									545
									200
									alar t
									and the
		a managed city							A COL
									20
									10
						1 1 1 2		1	60 15
									TEST TEST
									di l'Est lo
									ST ST ST
						*			1
				, a					

### (Set VIII)

The following are the conditions of licence number E/SC/KL/22/10(E85( 3) to possess for sale or use, explosives of Class 1,2,3, 4, 5, 6 and 7 in a magazine in Form LE-3 (at icles 3(b) to (c) ) granted by Chief controller of Explosives or Controller of Expl sives.

- The quantity of explosives on the premises at any one time shall not exceed the licensal 'e capacity.

  The magazine used for storage of explosives shall maintain safety distance specified 'n Schedule III and annexure to
- the licence.

  The magazine shall be used only for keeping all explosives specified in this licence at 1 of receptacles for, or tools or implements for work connected with the keeping of such explosives.

  The opening of packages and the weighting and pack not explosives shall not be carri 4 on in the magazine. Two or more description or explosives which may be permitted to be kept in the magaz se shall be kept only if they are separated from each other by an intervening partition of such substance or character, to be such intervening space, as (d) the various explosives of Class 2 (nitrate-mixture), Class 3 (nitro-com sound), sat 1 y fuses belonging to Class 6 Division 2 as do not contain any exposed from or steel, may be (e) Detonators belonging to Class 6 Division 3 shall be kept separately.

  (f) Gun powder belonging to Class 1 shall be kept separately.

  Explosives of Class 3 (nitro-compound) shall not be kept in the magazine after the expiration of one year from the date

- (f) Gun powder belonging to Class I shall be kept separately.

  Explosives of Class 3 (nitro compound) shall not be kept in the magazine after the expiration of one year from the date of their manufacture except with the special sanction of licensing authority.

  Explosives of Class 3 (nitro compound) shall not be kept in the magazine after the expiration of their manufacture except with the special sanction of the Controller of Explosives.

  (i) When such sanction has been given, a written certificate showing the period covered by the sanction shall be obtained from the Controller of Explosives at each inspection, and shall be kept by the licensee and produced on demand.

demand.

(ii) When an explosive owing to its being no longer of star dard purity or owing to sign of liquefaction or of exuded nitro-glycerin or liquid nitro-glycerin or liquid nitro-glycerin or liquid nitro-glycerin or store in the magazine or store house the licensee shall comply, at his own expense, with such directions as to its disposal as the Chief Controller or Controller of Explosives may issue.

The interior of the magraine and the benches, shelves and fittings therein shall be so constructed or so lined or covered The interior of the magazine and the benches, shelves and fittings therein shall be so controlled or so lined or covered as to prevent the exposure of any iron or steel contact with the explosives. Such interior, benches, shelves and fittings shall so far as is reasonably practicable, be kept free from grit and shall otherwise be explosives liable to be dangerously affected by water, due precautions shall be taken to explosive of the so much of this condition as relates to precautions against the exposure on piron or steel shall not be obligatory in a building in which no explosive other than explosive of the 1st Livision 6th. Ammunition Class is kept. The even of the test proving unsatisfactory, the same fees shall be payable by the licensee shall pay to the lighting conductor is passed by the testing officer as satisfactory:

Provided that the fees payable for a single test shall be charged for all tests made on a conductor during any one day:

Provided that the fees payable for a single test shall be charged for all tests made on a concector during any one day

Provided further that where two or more lighting conductors are attached to one and the same magazine, the fee for the testing of all such concuctors shall not exceed the fee prescribed in this condition 1 r testing a single lighting

Due provisions shall be made, by the use of suitable working clothes without pockets, suit ble shoes and by s Due provisions shall be finde, by the use of suitable working clothes without pockets, suit bie shoes and by searching or of otherwise or by such means, for preventing the introduction into danger area of the factory premises of fie, Lucifer matches or any substance or article likely to cause explosion or fire, but this condition in shall not prevent the introduction of an artificial light of such construction, position or character as not to couse any danger of fire or

Provided that so much of this condition as applies to the exclusion of iron or steel, shall no be obligatory in a building Provided that so much of this condition as applies to the exclusion of iron or st. et, shall no in which no explosive other than an explosive of the 1st Division of the 6th (An munition) that the increase shall keep records and accounts of all explosives in Forms RE-3 and RE-4 or and exhibit the stock books and records to any of the officers authorised under the Explosives which the stock books and records to any of the officers authorised under the Explosives (RE-5, as the case may be such officer may call upor him to do so. The stock books in the prescribed proferma shall or become shall be carried out to the premises without prior app oval of the licenses shall comply with any condition that may be specified by the licensing authority in the license shall report to licensing authority for inthivith, if the magazine becomes unfit for storage of any explosives or any explosives or the license of the magazine shall submit quarterly return as per sub-rules (3) and (4) of rule 24 of these rules.

Any encroachment of the safety distance shall be immediately communicated to the licens

- 16. The licensing authority shall be immediately informed for advice if any ε plosive is found deteriorated or
- unserviceable.

  17. The explosive packages shall be stocked in such a way so as to allow movement of at least one person to check the condition of all packages stored and to read the manufacture particulars of each pactage.

  The resistance of the lightning conductor to earth shall be as low as postible and in ocase be more than 10 ohms.

  18. The resistance of the lightning conductor to earth shall be as low as postible and in ocase be more than 10 ohms.

  19. A distance of 15 meters surrounding the magazine or store house hall be ket clear of dried grass or bush or flammable materials.

- Tammapie materials.

  Description of the explosive at the time of bringing inside the magazine shall be examined for its sound condition.

  The licensee and the employee shall be conversant with procedure so be taken during the emergency within the promises.
- 23. The licensee and the employee shall be given at all reasonable t nes to any aspecting or sampling officer and every facility shall be afforded to the officer for ascertaining that the provisions of the Act and these rules and the safety conditions are duly observed.
   24. Free access to the licensed premises shall be given at all reasonable t nes to any aspecting or sampling officer and every facility shall be afforded to the officer for ascertaining that the provisions of the Act and these rules and the license authority or a Controller of Explosives informs in writing, the higher facility of the license to execute any action of the license to execute any action of the license authority or a Controller of Explosives informs in writing, the higher facility of the license to execute any action of the license to execute any action of the license authority or a Controller of Explosives informs in writing, the higher facility of the license and the license and the license action of the license and the license action of the license and the license and the license action of the license and the license action of the license and the license action of the license action of
- safety conditions are duly observed.

  25. If the licensing authority or a Controller of Explosives informs in writing, the hider of the licence to execute any repairs or to make any additions or alterations to the licensed premise or machin ry, tools or apparatus or carry out safety of either on-site or off-site of the premises or persons, the holder of the license shall execute the recommendations and report compliance within the period specified by such authority.

  26. The licensee shall purchase authorised explosives from a licensed factory or company for possession and sale if any the magnitude of the license shall execute the explosives from a licensed factory or company for possession and sale if any the magnitude of the license shall execute the splosives from a licensed factory or company for possession and sale if any the magnitude of the license shall execute the splosives from a licensed factory or company for possession and sale if any the magnitude of the license shall execute the splosives from a licensed factory or company for possession and sale if any the magnitude is a specific profit of the license of the license shall execute the splosives from a licensed factory or company for possession and sale if any the magnitude is prohibited.

  30 [10 (M) dB, where N = number of crackers join a together.

  31 [22 (M) dB, where N = number of crackers join a together.

  32 [33 (M) dB, where N = number of crackers join a together.

  33 [34 (M) dB, where N = number of crackers join a together.

  34 [35 (M) dB, where N = number of crackers join a together.

  35 [36 (M) dB, where N = number of crackers join a together.

  36 [37 (M) dB, where N = number of crackers join a together.

  37 [38 (M) dB, where N = number of crackers join a together.

  38 [37 (M) dB, where N = number of crackers join a together.

  39 [37 (M) dB, where N = number of crackers join and together.

  30 [38 (M) dB, where N = number of crackers join and together.

  30 [38 (M) dB, where N = number of crackers join and together.

  31 [39 (M) dB, where N

For Je at Chief Controller of Explosives

3 q gray factor quality quality paid

For Deputy Chief Controller of Explosives एरः चलम / Ernakulam

# Form DE-2 (See rule 113 of the Explosives Rules, 2008) (Distance Form to be attached to the licence) Safety distances required to be kept clear around magazine for high explosives or fire wor is or factory licence number E/SC/KL/22/10(E8569) in form LE-3 granted to Shri K.A. ABRAHAM MG. DIRECTOR M/s. POABSON GRANITE PRODUCTS PVT. LTD., Thelakkad P.O. PERINTHALMANNA, MALAPPULAM DIST: ICT, KERALA, Kerala-. Type of Structure(s) Saf y distances meters Inside Safety Distances(ISD) Room or Workshop used in Connection with the Magazine Any other Explosives Magazine or store House or Factory of the Applicant Magazine Office 19 29 Middle Safety Distances(MSD) Middle Safety Distances(MSD) Middle Safety Distances(MSD) Magazine Keeper's or Chowkidar's Dwelling house Railway including Minerals and Private Railways Canal (in active use) or other navigable water Dock or Pier or Jetty Public Highway or Public Road Private Road which is PRINCIPAL means of access to a Temple, Mosque, Ch. rch, Gurudwara or other places of worships, Hospital, College, School or Factory River Embankment or Sea Embankment or Public Well Reservoir or Bounded tank/rope way Windmillor or Solar panel for Power Generation 48 Outside Safety Distances(OSD) Outside Safety Distances(OSD) Distances (OSD) Welling House Govt. and Public Building Temple, Mosque, Church or Gurudwara or other Places of Worshins Market place, Public recreation and Sports Ground, College, School, Hospital, Theater, Cinema or other Building where the public are accustoned to assemble 17 Factory 18 Buildings or Works used for the Storage in Bulk of Petroleum, Sprit, gas, or other inflammable or hazardous substances 95 19 Building or Works used for Storage and Manufacture of Explosives or of a sicles which contain Explosives 20 Aerodrome 21 Furnace, Kiln or Chimney 22 Quarry or mine pit head 23 Power House or Electric Substation 24 Wireless Station 25 Warehouse or other Storage Building 26 Any other Protected works 27. Electric Power over head Transmission Lines above 440V 28. Electric Power over head Transmission Lines upto 440V The Date: 12/05/1995 For J int Chief Controller of Explosives South Circle, Chennai Amendments: Amendment of Quantity of Explosives/Monthly Purchase L mit dated : 20/C5/2011 Amendment of Quantity of Explosives/Monthly Purchase L mit dated : 09/C3/2012 Propuly Chief Controller of Explosives • Amendment of Quantity of Explosives/Monthly Purchase L.mit dated: 09/€3/2012 世 中國國際 / Ernakulam



LANDGRAB

reduct a security many grade output and control of the faithful state of Renda Charles (Act of Islaments (Registration and Registration) & ().

# SC verdict to have major impact on health sector

CONTINUE

TO primite employment of collision of the continue o



## State Govt intervention sought

EXPERTS ATHS SERVICE

## VIGILANCE COURT ORDERS VACB TO REGISTER CASE AGAINST FIVE PERSONS

SEXII S. Mart S. Mart C. Carrier.

SEX Substitutes and Martin S. M



IN REMEMBRANCE

. S candigraphy from the material wavenurs of Bear who now on the bial couldn't at Arm both, digiting the Deposition Control of the Teneral Sentence Possition and Stantan Salarday, amountment

Chief Minister-level talks must to solve inter-state water pacts: Chemithala

## Ways mulled to boost KSRTC profit

EXPREST NOWS SERVICE AND VEI

TOP ALTERTAL PROPERTY OF THE MARKET COMPANY ASSOCIATION OF THE MARKET COMP

## 'Modi should tender apology for making godman Swachh Bharar ambassador'

ENDREST REWS SERVICE A TRANS

Data Anni Men Common Co

asset details: of godmen, demands VS



Altian received content of the distinct from the greating the period there is NOVA in the part of the period of th

# INTELLED STATE WATER PAGES: Chemisthate The State water page of the State of State The State of State of State The State of

NUTSEE | 13 injured as bus rams shop | 13 injured as bus rams shop | 14 injured as bus rams shop | 15 injured as bus rams shop | 16 injured as bus rams shop

Further Name Steam of January 1997.

All the state of the

## Cowboy Park opened in Munnar

EPH65 E MENT STEPLE Z Pleis's Enterment price to significant to the control of th

## Poabson Granite Products Pvt. Ltd.

DESCRIPTION OF THE PROPERTY



## POABSON GRANITE PRODUCTS PVT. LTD.

Thelakkad P. O., Pattikkad Via, Perinthalmanna - 679 325

POABS (

Mulappuram Dt., Kerala. Ph. +91 - 4933 245120, 245189 E-mail: pmna@poabs in, www.msand in

TIN: 32100752474 CST 32100752474-C

Dba25/08/2017

The Secretary, Vettathoor Panchayat, Malappuram District, Kerala.

Sub:- Environment Clearance (E.C.) - Proposed Quarry project at Survey No. 59/2, at Vettathoor Panchayat, Kariyavattom Village, Perinthalmanna Taluk, Malappuram District, Kerala - Submission of the E.C. Order - Compliance to the condition of Environment Clearance - Reg.

Respected Sir,

This refers to the Environment Clearance obtained for our proposed quarry project at Survey No. 59/2, at Vettathoor Panchayat, Kariyavattom Village, Perinthalmanna Taluk, Malappuram District, Kerala issued by State Environment Impact Assessment Authority (SEIAA), Kerala vide Order No. 946/SEIAA/EC1/4152/2015 dt. 16/08/2017.

We hereby submit a self attested copy of the Environment Clearance Order No. 946/SEIAA/EC1/4152/2015 dt. 16/08/2017.

This is in compliance to the condition of the E.C. Order.

Kindly acknowledge the receipt of the same.

Thanking you,

Yours respectfully, For Poabson Granite Products Pvt. Ltd.,

K.A. Abraham, (Managing Director)

Encl: As above

Regd. Office: Kuttoor P. O., Tiruvalla, Kerala, India - 689 106, Ph. +91 - 469 2743300, Fax. +91 - 469 274333, E-mail: mail@coats.com

Secretary ettathur Grama Panchayath Malappuram=



കേരളം केरल KERALA

AX 756153

## AFFIDAVIT

- I, K.A. Abraham. Managing Director & Authorized Signatory of M/s. Poabson Granite Products Pvt. Ltd. having its correspondence office at Kuttoor P.O., Thiruvalla, Kera'a - 689 106 do hereby affirm and confirm as follows:-
  - That, M/s Poabson Granite Products Pvt. Ltd. proposes to develop a quarry project at Survey No. 59/2, at Vettathoor Panchayat, Kariyavattom Village, Perinthalmanna Taluk, Malappuram District, Korala.
  - That, the Environment Clearance proceedings number and date are Order No. 946/SEIAA/EC1/4152/2015 dt. 16/08/2017.

3. That, all the conditions stipulated in the Environment Clearance would be upulously followed.

DEPONENT

A.P. Gokula Chanum, roskiela. Advocate del iglasiy

Poabson Granite ?) RS. cool-

Abraham Managing Directors of Granile Problem De Ghinnes

कारमञ्जूष्टीक शराबाद्यक । य



കേരളം केरल KERALA

AX 756154

Verification:

Verified that my above statements are true to the best of my knowledge and belief and nothing material has been concealed therein.

DEPONENT

Place, Malappuram

Date: 25/08/2017

Scientify affirmed and signed before my by the negocial who is personally known to me in my office at Thirwalle on this the 2 day of 20

> A.P. Gokula Chandran, 8 F.M. B. Advocate & Notary Sed Holz /85/71 Thiomatic.

Sell Hotel #5/71 Th

Pombson Granite Products
Pombson Granite Products
Scal.

Tanaging Druder Products Produ

## Water, Air and Noise Analysis reports



Phone: 0484-2544030, 8281982322, 9747400085, 9747400089, www.poluchem.com, poluchem@gmail.com

ACCREDITED BY KSPCH AS "A" GRADE LABORATORY

## TEST REPORT

Ref.No. PL/RT/SW/13241/2019

Page 01 of 02 Date of Issue: 24/12/2019

Name & address of customer

: M/s Poabs Granite Product(P) Ltd

Thelakkad,Perinthalmanna Malappuram

Project Site

Sample drawn by

Sample description

: M/s Poabs Granite Product(P) Ltd

Sy.No.59/2

Village - Kariavattom Panchayath- Vettathoor Taluk-Perinthalmanna

District - Malappuram, Kerala

: Poluchem Laboratory Sample Collector : Water Sample

Location of sampling : Surface water
Date of sample collected : 19/12/2019
Date of analysis started : 19/12/2019
Date of completion of analysis : 23/12/2019

Parameters tested	Test method	Results	Acceptable Limit As Per IS 10500-2012	
Color	IS 3025 (P) 04 - 1983 RA2017	8 Hazen Unit	5 Hazen Unit	
Odour	IS 3025 (P) 05 - 1983 RA2017	Agreeable	Agreeable	
Turbidity	IS 3025 (P) 10 - 1984 RA2017	3 NTU	1 NTU	
pH	IS 3025 (P) 11 – 1983 RA 2017	6.24	6.5 - 8.5	
Total Dissolved Solids	IS 3025 (P) 16 - 1984 RA2017	74.6 mg/l	500 mg/l	
Total Hardness as CaCO <sub>3</sub>	ess as CaCO <sub>3</sub> IS 3025 (P) 21 – 1983 RA2014		200 mg/l	
Total Alkalinity as CaCO <sub>3</sub>	IS 3025 (P) 23 - 1986 RA2014	21.3 mg/l 16.8 mg/l	200 mg/l	
Residual Chlorine	IS 3025 (P) 26 - 1986 RA2014	BDL	0.2 mg/l	
Chloride as Cl	IS 3025 (P) 32 - 1988 RA2014	16.3 mg/l	250 mg/l	
Calcium as Ca	IS 3025 (P) 40 - 1991 RA2014	4.14 mg/l	75 mg/l	
Magnesium as Mg	IS 3025 (P) 46 - 1994 RA2014	2.61 mg/l	30 mg/l	
Total Iron as Fe	IS 3025 (P) 53 - 2003 RA2014	0.65 mg/l	0.3 mg/l	
Sulphate as SO <sub>4</sub>	IS 3025 (P) 24 - 1986 RA2009	7.42 mg/l	200 mg/l	
Fluoride as F	IS 3025 (P) 60 -2008 RA 2013	0.2 mg/l	1.0 mg/l	

Note: BDL - Below Detection Level

For Poluchem Laboratories (P) Ltd.

Authorized signatory



PALLATH BUILDING, N. KALAMASSERY P. O., ERNAKULAM - 683104

Page 02 of 02

13241/2019 Continuation of Test Certificate No:\_\_\_

	Parameters tested Test method		As per IS-10500-2012
	IS 3025 (P)56 -2003 RA2014	BDL	0.01 mg/l
Selenium as Se	IS 3025(P) 37–1988 RA2014	BDL	0.01 mg/l
Arsenic as As		BDL	0.05 mg/l
Copper as Cu	IS 3025(P) 42-1992 RA2014	BDL	0.1 mg/l
Manganese as Mn	IS 3025(P) 59-2006 RA2017	BDL	0.003 mg/l
Cadmium as Cd	IS 3025(P) 41– 1992 RA2014	BDL	· 0.05 mg/l
Chromium as Cr	IS 3025 (P)52 - 2003 RA2014		5 mg/l
Zinc as Zn	IS 3025 (P)49 - 1994 RA2014	BDL	0.001 mg/l
Mercury as Hg	IS 3025(P) 48 - 1994 RA2014	BDL	
Cyanide as CN	IS 3025(P)27-1986 RA2014	BDL	0.05 mg/l
Lead as Pb	IS 3025(P) 47-1994 RA2014	BDL	0.01 mg/l
Aluminum as Al	IS 3025(P) 55-2003 RA2014	BDL	0.03 mg/l
Boron as B	IS 3025(P) 57-2005 RA2017	BDL	0.5 mg/l

Note: BDL - Below Detection Level

## MICROBIOLOGY ANALYSIS

Parameters tested	Unit	Test method	Results	Acceptable Limit As per IS – 10500-2012
Coliforms	MPN/100ml	IS 1622: 1981 RA 2009	90	Absent
E coli	Present or Absent/100ml	IS 1622: 1981 RA 2009	Absent	Absent

For Poluchem Laboratories (P) Ltd.

Authorized signatory

\* End of the report\*

The above results are related only to the sample submitted for analysis. This test report shall not be reproduced except in full, without the written approval of the laboratory.



## POLUCHEM LABORATORIES (P) LTD.

CHEMICAL, ENVIRONMENTAL AND MICROBIOLOGY LABORATORY
PALLATH BUILDING, N. KALAMASSERY P. O., ERNAKULAM - 683104
Phone: 0484-2544030, 8281982322, 9747400085, 9747400089, www.poluchem.com, poluchem@gmail.com

ACCREDITED BY KSPCB AS "A" GRADE LABORATORY

## TEST REPORT

Ref.No. PL/RT/SW/13242/2019

Page 01 of 02 Date of Issue: 24/12/2019

Name & address of customer

: M/s Poabs Granite Product(P) Ltd

Thelakkad, Perinthalmanna

Malappuram

Project Site

: M/s Poabs Granite Product(P) Ltd

Sy.No.59/2

Village - Kariavattom Panchayath- Vettathoor Taluk-Perinthalmanna District - Malappuram, Kerala

Sample drawn by

: Poluchem Laboratory Sample Collector

Sample description Location of sampling Date of sample collected Date of analysis started : Drinking Water : Open Well Water : 19/12/2019

Date of analysis started

Date of completion of analysis

: 20/12/2019 : 24/12/2019

Parameters tested Test method	Results	Acceptable Limit As Per IS 10500-2012	
Color IS 3025 (P) 04 – 1983 RA2017	5 Hazen Unit	5 Hazen Unit	
Odour IS 3025 (P) 05 – 1983 RA2017	Agreeable	Agreeable	
Turbidity IS 3025 (P) 10 – 1984 RA2017	BDL	1 NTU	
pH IS 3025 (P) 11 – 1983 RA 2017	6.57	6.5 - 8.5	
Total Dissolved Solids IS 3025 (P) 16 – 1984 RA2017	65 mg/l	500 mg/l	
Total Hardness as CaCO <sub>3</sub> IS 3025 (P) 21 – 1983 RA2014	21.3 mg/l	200 mg/l	
Total Alkalinity as CaCO <sub>3</sub> IS 3025 (P) 23 – 1986 RA2014	19.2 mg/l	200 mg/l	
Residual Chlorine IS 3025 (P) 26 – 1986 RA2014	BDL	0.2 mg/l	
Chloride as Cl IS 3025 (P) 32 – 1988 RA2014	14.6 mg/l	250 mg/l	
Calcium as Ca IS 3025 (P) 40 – 1991 RA2014	6.32 mg/l	75 mg/l	
Magnesium as Mg IS 3025 (P) 46 – 1994 RA2014	2.14 mg/l	30 mg/l	
Total Iron as Fe IS 3025 (P) 53 – 2003 RA2014	0.21 mg/l	0.3 mg/l	
Sulphate as SO <sub>4</sub> IS 3025 (P) 24 – 1986 RA2009	3.6 mg/l	200 mg/l	
Fluoride as F IS 3025 (P) 60 -2008 RA 2013	0.15 mg/l	1.0 mg/l	

Note: BDL - Below Detection Level

For Poluchem Laboratories (P) Ltd.

Authorized signatory



# POLUCHEM LABORATORIES (P) LTD.

CHEMICAL, ENVIRONMENTAL AND MICROBIOLOGY LABORATORY
PALLATH BUILDING, N. KALAMASSERY P. O., ERNAKULAM - 683104

ACCREDITED BY KSPCB AS "A" GRADE LABORATORY

Page 02 of 02

Parameters tested	Parameters tested Test method		Acceptable Limits As per IS-10500-201	
Selenium as Se	IS 3025 (P)56 -2003 RA2014	BDL	0.01 mg/l	
Arsenic as As	IS 3025(P) 37-1988 RA2014	BDL	0.01 mg/l	
Copper as Cu	IS 3025(P) 42- 1992 RA2014	BDL	0.05 mg/l	
Manganese as Mn	IS 3025(P) 59-2006 RA2017	BDL	0.1 mg/l	
Cadmium as Cd	IS 3025(P) 41- 1992 RA2014	BDL	. 0.003 mg/l	
Chromium as Cr	IS 3025 (P)52 – 2003 RA2014	BDL	0.05 mg/l	
Zinc as Zn	IS 3025 (P)49 – 1994 RA2014	BDL	5 mg/l	
Mercury as Hg	IS 3025(P) 48 – 1994 RA2014	BDL	0.001 mg/l	
Cyanide as CN	IS 3025(P)27-1986 RA2014	BDL	0.05 mg/l	
Lead as Pb	IS 3025(P) 47-1994 RA2014	BDL	0.01 mg/l	
Aluminum as Al	IS 3025(P) 55-2003 RA2014	BDL	0.03 mg/l	
Boron as B	IS 3025(P) 57-2005 RA2017	BDL	0.5 mg/l	

Note : BDL – Below Detection Level
MICROBIOLOGY ANALYSIS

Parameters tested	Unit	Test method	Results	Acceptable Limit As per IS – 10500-2012
Coliforms	MPN/100ml	IS 1622: 1981 RA 2009	23_	Absent
E coli	Present or Absent/100ml	IS 1622: 1981 RA 2009	Absent	Absent

For Poluchem Laboratories (P) Ltd.

Authorized signatory

\* End of the report\*

The above results are related only to the sample submitted for analysis. This test report shall not be reproduced except in full, without the written approval of the laboratory.



POLUCHEM LABORATORIES (P) LTD. CHEMICAL, ENVIRONMENTAL AND MICROBIOLOGY LABORATORY PALLATH BUILDING, N. KALAMASSERY P. O., ERNAKULAM - 683104

## TEST REPORT

Page 01 of 01

Client Name & Address	Certificate No:	PL/AMB/RT/13240/2019 .
	Date of issue:	24/12/2019
	Date of monitoring	18/12/2019 10.00 Hrs to 19/12/2019 10.00 Hrs
M/s Poabs Granite Product(P) Ltd Thelakkad, Perinthalmanna	Date of sample received:	19/12/2019 .
Malappuram	Date of analysis	20/12/2019
Malappuram	Monitoring Location	M/s Poabs Granite Product(P) Ltd Sy.No.59/2 Village - Kariavattom Panchayath- Vettathoor Taluk-Perinthalmanna District - Malappuram, Kerala
	Sample description	Ambient air -Near east side boundary
	Sample code given by client	Nil

SL NO	PARAMETERS	TEST METHOD	RESULTS	Limit as per NAAQS
01	Particulate Matter (PM <sub>10</sub> )	I S 5182 Part 23 2006RA2012	57.1 μg/m³	100 μg/m³
02	Particulate Matter (PM <sub>2.5</sub> )	CPCB	31,3 μg/m³	60 μg/m³
03	Sulphur dioxide	I S 5182 Part 2 2001 RA 2017	6.3 μg/m <sup>3</sup>	80 μg/m <sup>3</sup>
04	Nitrogen dioxide	IS 5182 Part 06 2006 RA2017	5.1 μg/m <sup>3</sup>	80 μg/m <sup>3</sup>

Note: NAAQS-National Ambient Air Quality Standards

\* End of the Report\*

The results are related only to the sample collected for analysis. This certificate shall not be reproduced except in full and without the written permission with authorized signatory

For and on behalf of POLUCHEM LABORATORIES (P) LTD.

AUTHORIZED SIGNATORY